

Tasha



TASHA



TASHA

Super premium self-elevating cantilever drilling rig independent legs (jack up) - 15,000 Psi Blow Out Preventer System - 3 ea. 7,500 Psi WP Mud Pumps - 3,000 HP Drawworks

Design	: Friede Goldman Independent 3 Leg Cantilever Jack up: JU 2000E
Class	: ABS ✕ A1, Self Elevating Drilling Unit
Dimensions/ LOA	: 323.8 ft (98.7 m) x 250 ft (76 m) x 31 ft (9.6 m)
Maximum Water Depth	: 400 ft (122 m) - Leg length below hull 477 ft (145 m)
Drilling Capacity	: 25,000 ft (7,620 m with 5-1/2 inch DP)
Power Main engines	: Six (6) 3516 C-HD Caterpillar
Emergency generator	: One C 32 Caterpillar
Drawworks	: NOV ADS-10T 3000 HP rated 1.5M lbs with 14 lines – AC Variable Frequency Drive with KEMS system and 2ea disc brakes
Derrick	: Derrick D-170 1.5M Hookload. 170ft clear height, base 40x40 ft. [12.2 m x 12.2 m), Static hook capacity of 1,500,000 lbs.
Traveling block	: National Oilwell Varco, 1.500 kips [680m. tons) 750 short tons
Rotary table	: National Oilwell Varco, RST 49 1/2" 750 ton
Mud Pumps	: Three, (3 ea.) National Oilwell Varco, Model 14-P-220, 2200 hp, 7500 psi, 9" bore x 14" stroke
Top Drive	: TDS 8SA, NOV, <ul style="list-style-type: none">• 750 Short ton hoisting capacity (API 8C)• 1x 1,150 hp AC motor• 7,500 PSI working pressure• Max Continuous Torque 67,000+ ft-lbs, Max RPM: 260
Cyber Drilling Control	: One chair cabin with joystick, ADS Amphion Control System with Electronic Driller.
Iron Roughneck	: Varco ST-120 primary Iron Roughneck. Varco ST-80 for offline stand building
Mud tanks	: Active & Reserve Mud Pits 5,000 bbls [795cu.m], separate Brine tanks for 1,340 bbls [213 cu.m]. Slugging Pit Capacity 1 SO bbls [24cu.m)
Sack Storage	: 5,000 sacks
Mud Process	: Cascading Shaker System Gumbo Box Over Brandt Quint VSM 300 Shaker 5 ea Brandt finishing shale shakers, VSM 300 2 x Brandt DG-12 Degassers 1 x Desander (capacity 2,000 gpm); 1 x desilter (capacity 2,000 gpm); 1 x mud gas separator (capacity 40 mscf/d)
Fuel Capacity	: 4,150 bbls [660 cu.m)
Diverter System	: 1 ea. HYDRIL MSP, 29 ½", 500 psi WP
BOP	: 2 ea. x 18 ¾" Shaffer Double Ram 10,000 Psi OR 13 5/8 " Double Ram 15,000 Psi 1 ea. x 18 ¾" Shaffer Annular 5,000 Psi OR 13 5/8 " Annular 10,000 Psi Choke Manifold: 15,000 psi, 2 kill and 2 choke line 3"
Drilling Pattern	: 75 ft x 30 ft
BOP Control	: Electro Flow Controls (EFC) BOP control unit
BOP Testing	: 2 ea. BOP stumps and 1 unit 20K test pump
Crane	: 3 ea. Liebherr, Pedestal mounted 75 Ton deck cranes, electro hydraulic with 120 ft booms, load monitoring and alarm
Cantilever Deck Crane	: Manufacture : TTS Bohai, GP 735-15-28, pedestal mounted 10.5 tons @all radius, powered by EX/Electric over hydraulic
Helideck	: Design for Sikorsky S-61-N
Living Quarters	: 140 persons

PT Apexindo Pratama Duta Tbk

Head Office : Office 8 20th – 21st Floor, SCBD Lot 28 JL. Jend. Sudirman Kav. 52-53 , Jakarta 12190
Tel. (62-21)29333000 , 29333020 (Hunting) Fax. (62-21) 29333111
Email: info@apexindo.com

Branch Office : Jl. Jend. Sudirman, Balikpapan Permai Complex, Blok L No. 10-12, Balikpapan 76114
Tel. (62-542) 410 258 (Hunting) Fax. (62-542) 411 788

Contact Person : Donald Kent Wood (Director/ Independent Director)